universität innsbruck

WS 2026/2027



Advanced Functional Programming

Week 3 – Type-Inference in Haskell, Kinds and Explicit Foralls

René Thiemann

Department of Computer Science

Type-Inference in Haskell

Last Week: Type-Inference Algorithm of Hindley and Milner

- assign one type variable to term variables and to arguments of newly defined function
  - `f :: a1 -> a2 -> a3`, `x :: a4`, ...
- each type variable in previously defined function in Γ is replaced by fresh one
  - `(:) :: a5 -> [a5] -> [a5]` for one occurrence of `(:)`, and
    `(:) :: a6 -> [a6] -> [a6]` for another occurrence of `(:)`
- assign type variable to each non-atomic subterm
  - `(:) x :: b1`, ...
- constraints ensure that applications are well-typed
  - `a5 -> [a5] -> [a5] = a4 -> b1` for application `(:) x`, ...
- unification detects type-problem or results in most general type
  `f :: (a1 -> a2 -> a3)`τ
- finally, `f :: (a1 -> a2 -> a3)`τ is added to context Γ
- simplified presentation: original algorithm merges constraint generation and unification

When to Instantiate Type Variables?

- after a function `f :: ty` has been type checked,
  future uses of `f` can instantiate the type variables: `f :: ty`τ

```
twice :: a -> [a]
twice x = [x, x]
test1 = (twice True, twice (twice (5 :: Int)))
```

- this also happens for locally defined functions within a `let`

```
test2 = let twiceLocal x = [x, x] in (twiceLocal True, twiceLocal 'c')
```

- in contrast, variables in λ's or variables in lhss are restricted to one type during type checking; therefore the following functions are not well-typed

```
createGen1 p = (p True, p 'c')       -- not allowed
createGen2 = \ p -> (p True, p 'c')  -- not allowed
test3 = createGen1 twice
test4 = createGen2 twice
```

Instantiations with Explicit Type Annotations

- consider the following program

```
typingTest 0 x y = x
typingTest n x y =
  if typingTest (n - 1) True (x > y)
  then y
  else typingTest (n - 1) y x
```

- using type inference without given type for `typingTest`
  - third line: `typingTest` takes Booleans as second and third argument
  - inferred type: `(Eq a, Num a) => a -> Bool -> Bool -> Bool`
- using explicit type annotation

```
typingTest :: (Eq a, Num a, Ord b) => a -> b -> b -> b
```

  - in each occurrence of rhs, `typingTest` can be instantiated differently
    - line 3: `b = Bool`
    - line 5: `b = b`
  - overall, get more general type than by type inference alone
  - sometimes, typing is not possible without explicit annotation

Order of Type-Inference

- consider program containing definitions of functions $\texttt{f}_1$, $\texttt{f}_2$, ...
- for type-inference, first a call-graph is constructed and call-dependencies are tracked
- whenever $\texttt{f}_i$ calls $\texttt{f}_j$, but not vice-versa (directly or indirectly), then $\texttt{f}_j$ is type-checked before $\texttt{f}_i$
  - consequence: type of $\texttt{f}_j$ can be instantiated when type-checking $\texttt{f}_i$
- mutually recursive functions are type-checked at the same time
- example

```
f x = if x == 0 then g h else g (g (f (x - 1)))  -- f calls g,h
h = g (f 5)                                      -- h calls f,g
g x = x . x
j c = if c == 'a' then 'z' else i c              -- j calls i
i c = pred c
```

- order: $\texttt{i} < \texttt{j}$ and $\texttt{g} < \{\texttt{f}, \texttt{h}\}$

Types, Type-Expressions and Kinds

Expressions Revisited

- grammar describes building rules of expressions
  - variables are expressions
  - if f is n-ary function and $e_1, \ldots, e_n$ are expressions, then so is $f\ e_1\ \ldots, e_n$ (first order)
  - function names are expressions (higher order)
  - if e_1 and e_2 are expressions then so is $e_1\ e_2$ (higher order)
  - if x is a variable and e is an expression then so is $\lambda x \to e$ (higher order)
- restriction to well-typed expressions `expr :: ty`

Types Revisited

- grammar describes building rules of types
  - variables are types
  - if c is n-ary type-constructor and $t_1, \ldots, t_n$ are types, then so is $c\ t_1\ \ldots, t_n$ (first order)
- example: `Either (Int, Bool, Char) [[String]]`
- missing: generalization to higher-order types
- missing: what are well-typed types? `ty :: ???`

Type-Expressions: Higher-Order Types

- generalize grammar for types to higher-order: partial application
- types (or type-expressions) are build as follows
  - variables are type-expressions
  - type-constructors are type-expressions
  - whenever te_1 and te_2 are type-expressions, then so is $te_1\ te_2$
- there is no λ for type-expressions
- examples
  - `Either (Int, Bool, Char)` is a type expression
    (recall: `data Either a b = Left a | Right b`)
  - `a b` is a type expression
  - `(a b){a/Either (Int, Bool, Char)}` is the type `Either (Int, Bool, Char) b`
- notion used in this course
  - type expressions: as defined by grammar above
  - types: type expressions without partial application
  - clarification: next slides

Kinds: The Type of Type Expressions

- kinds are used to describe the structure of types
- kind-inference determines whether some type(-expression) t has kind k, written `t :: k`
- kinds themselves are formed as follows
  - `*` is a kind, representing types, but not partially applied type expressions
  - if `k1` and `k2` are kinds, then so is `k1 -> k2`
- examples
  - `t :: *` means that `t` is a type
    - `Int`, `[Bool]`, `a -> a`, etc.
  - `t :: * -> *` means that `t` is expecting one argument (a type) to become a type
    - `Maybe`, `[]`, `(->) Int`, `Either Bool`
  - `t :: * -> * -> *` (identical to: `* -> (* -> *)`)
    - `t` is a type-expression that expects two types to deliver a type
    - `Either :: * -> * -> *`
    - `(->) :: * -> * -> *`, the function type constructor needs two types

Kinds Continued

- often n-ary type constructor have kind `* -> * -> ... -> * -> *`
  where there are n many `->`
- example type constructors
  - arity 0: `Int`, `Integer`, `Char`, `Double`, `()`, `Bool`, `Ty` where `data Ty = ...`
  - arity 1: `Maybe`, `Set`, `[]` (the list-type constr.), `Ty` where `data Ty a = ...`
  - arity 2: `Either`, `Map`, `(->)` (the function-type constr.), `Ty` where `data Ty a b = ...`
- rule for determining kinds using some context Γ
  - whenever $\Gamma \vdash$ `ty1 :: k1 -> k2` and $\Gamma \vdash$ `ty2 :: k1` then $\Gamma \vdash$ `ty1 ty2 :: k2`
  - $\Gamma \vdash$ `a :: k` whenever `a :: k` $\in \Gamma$ for every type variable `a` and kind `k`
- example: `Either Int :: * -> *`, since `Either :: * -> (* -> *)` and `Int :: *`
- example: try `:k Either Maybe` in ghci
- remark: also type-classes have a kind, using the special kind `Constraint`
  - `Show, Num, Eq, Ord :: * -> Constraint`
  - classes of shape `class C a b where ...` often have kind `* -> * -> Constraint`

Higher-Order Kinds

- consider `data Ty a b = ...`
- often such a datatype definition results in `Ty :: * -> * -> *`
- however, this is not always the case, since we might have higher-order kinds
- example: `data Ty a b = Con (a b)`
  - here, `a :: * -> *`, since `a` is applied on `b`
  - this is automatically inferred using kinds-inference
  - consequently: `Ty :: (* -> *) -> * -> *`
  - `Ty` takes a unary type constructor (or more precisely: any type expression of kind `* -> *`) and a type to deliver a type
  - example: `Ty Maybe Int :: *` and `Con (Just 5) :: Ty Maybe Int`
- we will see that even standard libraries utilize higher-order kinds
- example: `:t minimum, :k Foldable`

Example using Higher-Order Kinds

- week 1 already used types and type-classes with higher-order kinds (docu arrays)

```
class IArray a e where
  bounds :: Ix i => a i e -> (i,i)
  ...
```

- from the type `a i e` we infer
  - `a :: * -> * -> *`
  - `i :: *`
  - `e :: *`
- consequently, class `IArray` requires as arguments
  - something of kind `* -> * -> *`, e.g., a binary type constructor `a` (the array constructor),
  - and an element type `e`
- in total: `IArray :: (* -> * -> *) -> * -> Constraint`
- example instantiation:
  `instance IArray Array e`
  (the type-constructor `Array` implements `IArray` for every element type `e`)
- starting next week, we will see further type-classes using higher-order kinds

Language Extensions Involving Explicit Forall

Quantification of Type Variables

- consider polymorphic function, e.g., `map :: (a -> b) -> [a] -> [b]`
- type variables are implicitly universally quantified

  we may substitute `a` and `b` by all types
- some Haskell extension allows us to make universal application explicit by keyword forall

  `map :: forall a b. (a -> b) -> [a] -> [b]`

Language Extensions

- supported by GHC, extend the Haskell standard
- need to be activated explicitly
  - activation at the beginning of a Haskell file

    `{-# LANGUAGE ExplicitForAll, ... #-}`
  - or project-wide activation in cabal-file

    `default-extensions: ExplicitForAll, ...`
- just for type-system, there are several extensions

  https://ghc.gitlab.haskell.org/ghc/doc/users_guide/exts/types.html

Extension of Scoped Type Variables

- consider the following Haskell code

```
sortRev :: forall a. Ord a => [a] -> [(a, a)]
sortRev xs = zip sorted reversed where
  sorted :: [a]
  sorted = sort xs
  reversed :: [a]
  reversed = reverse xs
```

- this program does not type check without suitable language extensions
- reason: in each of the three type annotations, the `a` is implicitly quantified, so it is equivalent to use annotations `sorted :: [a1]`, `reversed :: [a2]`
- using extension `ScopedTypeVariables`, the `forall a` binds all `a`'s in the function body, including the `where`-blocks
- then the above code compiles, since all type annotations refer to the same type variable `a`
- remark: activating `ScopedTypeVariables` implicitly activates `ExplicitForAll`

Existential Types

- consider a polymorphic (universally quantified) function such as
  `map :: forall a b. (a -> b) -> [a] -> [b]`
- view point from user of `map`
  - polymorphism: ability to substitute `a` and `b` by more concrete types
  - the more generic the type is, the more flexible it can be used
- view point from implementation of `map`
  - type variables `a` and `b` cannot be instantiated, represent unknown types
  - the more generic the type is, the less one can perform
  - example: there are only two functions of type `a -> a`
- existentially quantified types: change role of user and implementation
  - implementation can instantiate type variables
  - user needs to provide polymorphic input

Example Application: Generic Logger

- consider application, that processes many different kinds of data
- certain events should be logged, each event might have different type
- logging method should be parametric, e.g., log to stdout, log to file, no logging, etc.
- application in Haskell

```
appl :: ??? -> IO ()
appl log = do
  inputs <- readFile "inputs.txt"
  ...
  log "init DB access"
  ...
  log ("login failed", user, timeStamp)
  ...
  log (Transaction client1 amount client2)
  ...
```

- current type-inference algorithm will fail;
  three incompatible input arguments: a string, a triple, and a custom datatype

Towards Existential Types in Haskell

- consider first order logic
  1. $P(a) \to Q(f(b))$
  2. $\forall b\ a.\ (P(a) \to Q(f(b)))$
  3. $\forall b.\ ((\forall a.\, P(a)) \to Q(f(b)))$
- formulas 1 and 2 are equivalent (using implicit universal quantification of free variables)
- formula 3 is different, since the $\forall$ is put to the left of an implication
- in fact, formula 3 is equivalent to formula 4 with an existential quantifier
  4. $\forall b.\ \exists a.\ (P(a) \to Q(f(b)))$
- observation: using $\forall$ inside left argument of an implication leads to an $\exists$ on top-level
- formulas 1 and 2 have quantifier alternation depth 1
- formulas 3 and 4 have quantifier alternation depth 2
- now, let us do the same as in formula 3 in Haskell to obtain existentially quantified types
  - $\forall$ = `forall` and $\to$ = `->`
  - quantifier alternation depth = rank

Rank

- types without type-variables have rank 0
- types with (implicitly) universally quantified variables have rank 1
- type has rank 2 if it contains a rank-1 type on the left of ->
- type has rank 3 if it contains a rank-2 type on the left of ->
- ...
- examples
  - rank 1: `(a -> b) -> [a] -> [b]` and `forall a. Show a => a -> a -> String`
  - rank 2: `Ord b => [b] -> (forall a. Show a => a -> String) -> Int -> b`
  - rank 3: `(forall b. (forall a. a -> c -> a) -> [b] -> c) -> Maybe c -> c`
- extension `RankNTypes` enables user to specify types with arbitrary rank
- type-inference with arbitrary ranks is undecidable
- rule of thumb
  - whenever an explicit `forall` is required, then type has to be user-provided
  - automatic type-inference only works if inferred types have rank of at most 1

Free Usage of Forall in Type Definitions of Haskell: Existential Types

- swaps role of implementation and user of function
- example assumes type `fun :: (forall a. Ord a => [a] -> a) -> ... -> ...`
  - implementation of `fun` can instantiate `a`, e.g.,
    `fun g x = ... g [True, b] ... g [1,7,3]`
  - user of `fun` needs to pass polymorphic function, e.g.,
    `... fun minimum ...` or `... fun head ...` or `... fun (\ xs -> xs !! 5) ...`
  - the following invocations are not possible
    - `... fun and ...` — `and :: [Bool] -> Bool` is not generic enough
    - `... fun sum ...` — `sum :: Num a => [a] -> a` is not generic enough
- generic logger on slide 18 is now typable:
  `appl :: (forall a. Show a => a -> IO ()) -> IO ()`
- also `createGen1` and `createGen2` on slide 4 are typable

Generic Logger – Finalized

- type of application
```
appl :: (forall a. Show a => a -> IO ()) -> IO ()
```
- implement different logger algorithms in Haskell
```
noLog x = return ()
logToFile f x = appendFile f (show x ++ "\n")
logStdOut x = putStrLn $ "log: " ++ show x
```
- combine application with logger at the very end
```
main1, main2, main3 :: IO ()
main1 = appl noLog
main2 = appl (logToFile "log.txt")
main3 = appl logStdOut
```

Typing of `createGen1` and `createGen2`

```
createGen1, createGen2 :: (forall a. a -> b a) -> (b Bool, b Char)
createGen1 p = (p True, p 'c')
createGen2 = \ p -> (p True, p 'c')

testList1, testList2 :: ([Bool], [Char]) -- b = []
testList1 = createGen1 (\ x -> [x,x])
testList2 = createGen2 (\ x -> [x,x])

testMaybe :: (Maybe Bool, Maybe Char) -- b = Maybe
testMaybe = createGen1 Just
```

Limits of Higher-Order Type Expressions in Haskell

```
createGen1 :: (forall a. a -> b a) -> (b Bool, b Char)
createGen1 p = (p True, p 'c')

testList = createGen1 (\ x -> [x, x])
testMaybe = createGen1 Just
testInt = createGen1 (\ _ -> 42)
```

- the output type of `p` may depend on `a`: indicated by using `b a`
- there is no λ-abstraction and β-reduction on types, but just partial application;
  result: we cannot instantiate `b = \ _ -> Int` and simplify `(\ _ -> Int) a` to `Int`
- consequently, `testInt` is not typable, as `(\ _ -> 42) :: forall a. a -> Int` which is not compatible with `forall a. a -> b a`, no matter how we choose `b`
- workaround via `Const` type

```
newtype Const a b = Const a -- predefined in module Data.Functor.Const
testInt :: (Const Int Bool, Const Int Char)
testInt = createGen1 (\ _ -> Const 42)  -- b = Const Int
```

Literature

- Christopher Allen and Julie Moronuki: Haskell Programming from first principles, Chapter 11.4: "Type constructors and kinds"
- Simon Thompson, The Craft of Functional Programming, Second Edition, Addison–Wesley, Chapter 13: "Checking Types"
- Haskell Report 2010, Chapters 4.5 and 4.6, https://www.haskell.org/onlinereport/haskell2010/
- https://ghc.gitlab.haskell.org/ghc/doc/users_guide/exts/types.html
- https://serokell.io/blog/universal-and-existential-quantification