universität innsbruck

WS 2026/2027



Advanced Functional Programming

Week 4 – Functors, Record Syntax, Case Study: A Simple Parser

René Thiemann

Department of Computer Science

Last Week

- generalization of types: higher order type-expressions using partial application
  - type-expressions can be used in function definitions and in type-class definitions
  - kinds are used to "type" type-expressions
  - example

```
class IArray a e where
  bounds :: Ix i => a i e -> (i,i)

ghci> :k IArray
IArray :: (* -> * -> *) -> * -> Constraint
```

- explicit `forall` can be used for existential quantification
  - implementation can choose how to instantiate type variables of parameter
- using `forall` requires user-specified types
  - automation cannot infer `forall`s automatically
  - type-inference is undecidable with explicit foralls

Functor

map

- consider the following Haskell source

```
sqrtInt :: Int -> Double
sqrtInt x = sqrt (fromIntegral x)

sqrtList [] = []
sqrtList (x : xs) = sqrtInt x : sqrtList xs
```

- we clearly see that `sqrtList` just applies `sqrtInt` on every number in a list
- there are many more functions that process the elements in a list pointwise
- abstraction: program `map` once, and then apply it several times

```
map :: (a -> b) -> [a] -> [b]
map f [] = []
map f (x : xs) = f x : map f xs

sqrtList = map sqrtInt
upperString = map toUpper
...
```

mapTree

- now consider trees
```
data Tree a = Leaf a | Node (Tree a) (Tree a) deriving Show

sqrtTree (Leaf x) = Leaf (sqrtInt x)
sqrtTree (Node l r) = Node (sqrtTree l) (sqrtTree r)
```
- we see that `sqrtTree` just computes the square-root of every number in the tree
- there are many more functions that might process a tree in the same way, i.e., performing pointwise updates in the tree
- abstraction: program `mapTree` once, and then apply it several times
```
mapTree :: (a -> b) -> Tree a -> Tree b
mapTree f (Leaf x) = Leaf (f x)
mapTree f (Node l r) = Node (mapTree f l) (mapTree f r)

sqrtTree = mapTree sqrtInt
upperTree = mapTree upperString
...
```


Functor

- clearly, there are strong similarities between `map` and `mapTree`
```
map     :: (a -> b) -> [a]     -> [b]
mapTree :: (a -> b) -> Tree a  -> Tree b
```
- we could also have written further map-functions for other types, e.g.
```
mapMaybe :: (a -> b) -> Maybe a -> Maybe b
```
- generalize common idea of structure preserving map-functions
  - consider some unary type-constructor `f` for containers over arbitrary type `a`, i.e., `f a` stores values of type `a`
  - a map-function `fmap` for `f` takes an arbitrary function of type `a -> b` in order to convert some `f a`-element to an `f b`-element in a way that
    - the structure is not altered (same shape of list, tree, ...)
    - `fmap id = id`
    - `fmap (g . h) = fmap g . fmap h`

    in this case we say that `f` is a functor
- examples
  - the list type-constructor is a functor, with `map` being the map-function
  - the tree type-constructor is a functor, with `mapTree` being the map-function

Functors in Haskell

- in Haskell it is possible to define a type-class to represent functors
```
class Functor f where
  fmap :: (a -> b) -> f a -> f b
```
- note: higher-order kinds are required: `Functor :: (* -> *) -> Constraint`
- instance declarations are as usual
```
instance Functor [] where
  fmap = map                    -- use existing function

instance Functor Tree where
  fmap = mapTree                -- use existing function

instance Functor Maybe where
  fmap g Nothing = Nothing      -- define map within functor instance
  fmap g (Just x) = Just (g x)
```
- observe: instances are type-constructors (`[]`, `Maybe`, ...), not types (`[a]`, `Maybe a`)

Functors in Haskell, Continued

- now it is possible to write one function which applies the square-root operation on arbitrary functors
```
fmapSqrt = fmap sqrtInt
```
- type: `fmapSqrt :: Functor f => f Int -> f Double`
- type-substitution: `fMapSqrt` has the following more concrete types
  - `fmapSqrt :: [Int] -> [Double]` `f = []`
  - `fmapSqrt :: Tree Int -> Tree Double` `f = Tree`
  - ...
- fact: for several types, there is no explicit named `map`-function such as `mapMaybe`, `mapTree`, but only the `fmap`-instance
- note: there is a `Set.map` function, but no `Functor` instance for `Set`
  - reason: `Set.map` is not structure preserving, i.e., it does not give rise to a functor
- view instances at `https://hackage.haskell.org/package/base/docs/Control-Monad.html#t:Functor`

Example of Using Functors, Syntax: `fmap` = `<$>`

- note that `fmap` is also available as infix `<$>` operator
  - `f $` applies a function `f` to an argument
  - `f <$>` applies a function `f` to values within container argument
- note the similarity of the unsafe and the safe version to compute $\lfloor \frac{x}{y} \rfloor^2$

```
safeDiv :: Int -> Int -> Maybe Int
safeDiv _ 0 = Nothing
safeDiv x y = Just (x `div` y)

unsafeSquareAfterDiv x y = (^2)  $  x `div` y
safeSquareAfterDiv   x y = (^2) <$> x `safeDiv` y
```


Functors of Non-Unary Type-Constructors

- consider types

```
data (a,b) = (a,b)
data (a,b,c) = (a,b,c)
data Either a b = Left a | Right b
```

- for all of these types, there is also a natural map-function
- there are two approaches in Haskell
- first approach: make a functor instance w.r.t. the last type variable

```
instance Functor (Either a) where
  fmap f (Left x) = Left x
  fmap f (Right y) = Right (f y)

instance Functor ((,) a) where
  fmap f (x,y) = (x, f y)

instance Functor ((,,) a b) where
  fmap f (x,y,z) = (x, y, f z)
```


Bifunctors

- second approach: use a bifunctor, map over last two type variables

```
class (forall a. Functor (p a)) => Bifunctor p where
  bimap :: (a -> b) -> (c -> d) -> p a c -> p b d
  first :: (a -> b) -> p a c -> p b c
  second :: (b -> c) -> p a b -> p a c
  first f = bimap f id
  second g = bimap id g

instance Bifunctor Either where
  bimap f g (Left x) = Left (f x)
  bimap f g (Right y) = Right (g y)

instance Bifunctor (,) where
  bimap f g (x,y) = (f x, g y)

instance Bifunctor ((,,) a) where
  bimap f g (x,y,z) = (x, f y, g z)
```


Case Study: Parsing PGM-Graphics

Parsing

- parsing
  - read some structured input format into internal representation
  - or report error
- examples
  - ghc parses Haskell source and converts it into abstract syntax tree; this is one of the first steps of the compilation process
  - browser parses HTML-file from server, and afterwards renders it
- parsers can be automatically generated in Haskell via `deriving Read`
  - however, then the input format will be Haskell expressions
  - in this course, we do not restrict to this approach
- generic idea of a parser for type `ty`
  - take input
  - consume first part of input and try to convert it to element `x :: ty`
  - return `x` and remaining input, or fail if some error occurred
- example in this section: parse PGM raw format for `.pgm` images (portable grey map)

PGM Raw Format

- PGM raw format has following structure
  - first two characters are "P5"
  - then there are three numbers separated by arbitrary amount of white space
    - width
    - height
    - maximal grey value
  - after the last of these numbers, a single white space character appears
  - finally the correct number of grey values of the image are provided as bytes
- example:

```
P5 1366  1036
 255
here the binary part starts
```



Representation of Output – Datatypes with Record Syntax

- store width, height, max grey value and binary grey values
- `data Greymap = Greymap Int Int Int L.ByteString`
  - is an obvious choice
  - might be confusing: order of `Int`s unclear
  - adding another entry will require to change patterns in function definitions
- data types can also use record syntax: more verbose, more flexible

```
data Greymap = Greymap {
      greyWidth :: Int
    , greyHeight :: Int
    , greyMax :: Int
    , greyData :: L.ByteString
    } deriving Eq

greyWidth :: Greymap -> Int
ex1 = Greymap { greyHeight = 10, greyWidth = 5, greyData = ..., ...}
ex2 = ex1 { greyHeight = 30 } -- update by name
```


Representation of Input

- input mixes ASCII and binary encoding
  - use Haskell `ByteString` as compact representation (uses arrays internally)
  - `ByteString`s can be read both in binary and in character-based mode
  - sometimes conversion required, e.g., between `String` and `ByteString`
- example code

```
import qualified Data.ByteString.Lazy.Char8 as L8  -- ASCII
import qualified Data.ByteString.Lazy as L         -- binary

L.readFile :: FilePath -> IO L.ByteString
L.drop :: Int64 -> L.ByteString -> L.ByteString
L.length :: L.ByteString -> Int64
L8.pack :: [Char] -> L.ByteString
L8.isPrefixOf :: L.ByteString -> L.ByteString -> Bool
L8.dropWhile :: (Char -> Bool) -> L.ByteString -> L.ByteString
L8.readInt :: L.ByteString -> Maybe (Int, L.ByteString)
```

- note: `L.ByteString -> Maybe (a, L.ByteString)` is type of parser for a-values

An Ad-Hoc Parser for PGM P5 Files

```
parseP5 :: L.ByteString -> Maybe (Greymap, L.ByteString)
parseP5 s =
  case matchHeader (L8.pack "P5") s of
    Nothing -> Nothing
    Just s1 ->
      case getNat (dropSpace s1) of
        Nothing -> Nothing
        Just (width, s2) ->
          case getNat (dropSpace s2) of
            Nothing -> Nothing
            Just (height, s3) ->
              case getNat (dropSpace s3) of
                Nothing -> Nothing
                Just (maxGrey, s4)
                  | maxGrey > 255 -> Nothing
                  | otherwise ->
                      case getBytes 1 s4 of
                        Nothing -> Nothing
                        Just (_, s5) ->
                          case getBytes (width * height) s5 of
                            Nothing -> Nothing
                            Just (bitmap, s6) -> Just (Greymap width height maxGrey bitmap, s6)
```


An Ad-Hoc Parser for PGM P5 Files – Auxiliary Functions

```
dropSpace = L8.dropWhile isSpace

matchHeader :: L.ByteString -> L.ByteString -> Maybe L.ByteString
matchHeader prefix str
    | prefix `L8.isPrefixOf` str = Just (L.drop (L.length prefix) str)
    | otherwise = Nothing

getNat :: L.ByteString -> Maybe (Int, L.ByteString)
getNat s = case L8.readInt s of
             Nothing -> Nothing
             Just (num,rest)
                 | num < 0   -> Nothing
                 | otherwise -> Just (fromIntegral num, rest)

getBytes :: Int -> L.ByteString -> Maybe (L.ByteString, L.ByteString)
getBytes n str = let count           = fromIntegral n
                     both@(prefix,_) = L.splitAt count str
                 in if L.length prefix < count
                    then Nothing
                    else Just both
```


Problems of Ad-Hoc Parser

- problem 1: repetitive case-analysis on Maybe-values
  - if we got a failure, then fail
  - otherwise, extract the current input and proceed with the next parser
- solution: refactor by abstraction

- problem 2: direct pattern matching on pairs (parsed-value, remaining input)
  - if we want to make a more verbose parser, e.g., tracking failure positions, we have to change all occurrences of pairs within parser
- solution: refactor by abstraction and data-hiding

Solving Repetitive Case-Analysis

- general abstract scheme
  - if we got a failure, then fail
  - otherwise, extract the current input and proceed with the next parser
- idea of defining abstract scheme as function
  - first argument is optional current value
  - second argument is function how to proceed
- in Haskell

```
(>>?) :: Maybe a -> (a -> Maybe b) -> Maybe b
Nothing >>? _ = Nothing
Just v  >>? f = f v
```

Solving Repetitive Case-Analysis: Adjusted Parser

```
parseP5_take2 :: L.ByteString -> Maybe (Greymap, L.ByteString)
parseP5_take2 s =
    matchHeader (L8.pack "P5") s      >>?
    skipSpace                         >>?
    getNat                            >>?
    \(width, s1) -> skipSpace s1      >>?
    getNat                            >>?
    \(height, s2) -> skipSpace s2     >>?
    getNat                            >>?
    \(maxGrey, s3) -> getBytes 1 s3   >>?
    (getBytes (width * height) . snd) >>?
    \(bitmap, s4) -> Just (Greymap width height maxGrey bitmap, s4)

skipSpace :: L.ByteString -> Maybe L.ByteString
skipSpace s = Just (L8.dropWhile isSpace s)
```


Observations

- nested case-analysis is gone
- still two stylistic problems
  - state `s` (`s1`,`s2`,...) is explicitly passed around
  - pattern matching on pairs is still present
- both problems will be handled by abstract new type for parsers

A Datatype for Parsing

Parser-State and Parser

- parser-state stores input and offset
  - stored in dedicated datatype

```
data ParseState = ParseState {
      string :: L.ByteString  -- remaining input
    , offset :: Int64         -- location w.r.t. global input
    } deriving Show
```

- parser for elements of type `a` is a function from parser-state to either an error-message or a pair consisting of an `a`-element and a new parser-state
  - we encapsulate such a function in a separate type

```
newtype Parse a = Parse {
      runParse :: ParseState -> Either String (a, ParseState)
    }
```

  - using `newtype` at this point: constructor `Parse` is not visible at runtime

Chaining Parsers

- recall definition from previous slide

```
newtype Parse a = Parse {
    runParse :: ParseState -> Either String (a, ParseState)
  }
```

- design primitive for chaining two parsers for sequential composition

```
(==>) :: Parse a -> (a -> Parse b) -> Parse b
firstParser ==> secondParser  =  Parse chainedParser
  where chainedParser initState   =
          case runParse firstParser initState of
            Left err -> Left err
            Right (firstResult, newState) ->
                runParse (secondParser firstResult) newState
```

- both a `Parse a`-element and also `p1 ==> \ x -> p2 x` never execute the functions
- chaining two parsers without result dependence

```
(==>&) :: Parse a -> Parse b -> Parse b
p1 ==>& p2 = p1 ==> \_ -> p2
```


Four Basic Parsers

```
newtype Parse a = Parse {
    runParse :: ParseState -> Either String (a, ParseState) }
```

- the parser that always succeeds and does not alter the state

```
identity :: a -> Parse a
identity a = Parse (\s -> Right (a, s))
```

- the parser that always fails

```
bail :: String -> Parse a
bail err = Parse (\s -> Left $
           "byte offset " ++ show (offset s) ++ ": " ++ err)
```

- the parser that reveals the internal state

```
getState :: Parse ParseState
getState = Parse (\s -> Right (s, s))
```

- the parser that changes the internal state

```
putState :: ParseState -> Parse ()
putState s = Parse (\_ -> Right ((), s))
```


Another Primitive: Parsing a Single Byte

```
parseByte :: Parse Word8
parseByte =
    getState ==> \state ->
    case L.uncons (string state) of
      Nothing ->
          bail "no more input"
      Just (byte,remainder) ->
          putState newState ==>&
          identity byte
        where newState = state { string = remainder,
                                offset = newOffset }
              newOffset = offset state + 1

L.uncons :: L.ByteString -> Maybe (Word8, L.ByteString)
```


Switching to Characters: Parsing a Single Char

```
parseByte :: Parse Word8 -- previous slide
parseChar :: Parse Char  -- do not copy code of previous slide

w2c :: Word8 -> Char
w2c = chr . fromIntegral

parseChar :: Parse Char
parseChar = w2c <$> parseByte

-- requires Functor instance of Parse
instance Functor Parse where
    fmap f parser = parser ==> \result ->
                    identity (f result)
```

Parsing Multiple Bytes

```
-- look at the first byte, without consuming it
peekByte :: Parse (Maybe Word8)
peekByte = (fmap fst . L.uncons . string) <$> getState

-- parsing multiple bytes
parseWhile :: (Word8 -> Bool) -> Parse [Word8]
parseWhile p = (fmap p <$> peekByte) ==> \mp ->
               if mp == Just True
               then parseByte ==> \b ->
                    (b:) <$> parseWhile p
               else identity []

-- and using conversion from Word8 to other type
parseWhileWith :: (Word8 -> a) -> (a -> Bool) -> Parse [a]
parseWhileWith f p = fmap f <$> parseWhile (p . f)
```


Final Parser

```
parseRawPGM :: Parse Greymap
parseRawPGM =
    parseWhileWith w2c notWhite ==> \header -> skipSpaces ==>&
    assert (header == "P5") "invalid raw header" ==>&
    parseNat ==> \width -> skipSpaces ==>&
    parseNat ==> \height -> skipSpaces ==>&
    parseNat ==> \maxGrey ->
    parseByte ==>&
    parseBytes (width * height) ==> \bitmap ->
    identity (Greymap width height maxGrey bitmap)
  where notWhite = (`notElem` " \r\n\t")

-- clear structure
-- no handling of explicit states
-- assert, parseBytes, parseNat, skipSpaces: see next slides
```


Remaining Primitives (1/2)

```
skipSpaces :: Parse ()
skipSpaces = parseWhileWith w2c isSpace ==>&
             identity ()

assert :: Bool -> String -> Parse ()
assert True  _   = identity ()
assert False err = bail err

parseNat :: Parse Int
parseNat = parseWhileWith w2c isDigit ==> \digits ->
           assert (not (null digits)) "digit expected" ==>&
           let n = read digits in
           assert (show n == digits) "integer overflow" ==>&
           identity n
```


Remaining Primitives (2/2)

```
parseBytes :: Int -> Parse L.ByteString
parseBytes n =
    getState ==> \st ->
    let n' = fromIntegral n
        (h, t) = L.splitAt n' (string st)
        st' = st { offset = offset st + n', string = t }
    in assert (L.length h == n') "end of input" ==>&
       putState st' ==>&
       identity h

-- running a parser
parse :: Parse a -> L.ByteString -> Either String a
parse parser input = fst <$> runParse parser (ParseState input 0)
```

Literature

- Real World Haskell, Chapter 10