universität innsbruck

26W lecture 4



Automata and Logic

Aart Middeldorp and Johannes Niederhauser

Outline

1. **Summary of Previous Lecture**
2. **Minimization**
3. **Intermezzo**
4. **Weak Monadic Second–Order Logic**
5. **Further Reading**

Definitions

- regular expression α over alphabet Σ:

$$a \in \Sigma \qquad \epsilon \qquad \varnothing \qquad \beta+\gamma \qquad \beta\gamma \qquad \beta^*$$

- set of strings $L(\alpha) \subseteq \Sigma^*$ matched by regular expression α:

$$L(a) = \{a\} \qquad L(\varnothing) = \varnothing \qquad L(\beta\gamma) = L(\beta)L(\gamma)$$
$$L(\epsilon) = \{\epsilon\} \qquad L(\beta+\gamma) = L(\beta) \cup L(\gamma) \qquad L(\beta^*) = L(\beta)^*$$

- regular expressions α and β are equivalent $(\alpha \equiv \beta)$ if $L(\alpha) = L(\beta)$

Theorem

finite automata and regular expressions are equivalent:

for all $A \subseteq \Sigma^*$ A is regular $\iff$ $A = L(\alpha)$ for some regular expression α

Definitions

- homomorphism is mapping $h\colon \Sigma^* \to \Gamma^*$ such that $h(\epsilon) = \epsilon$ and $h(xy) = h(x)h(y)$
- if $A \subseteq \Sigma^*$ then $h(A) = \{h(x) \mid x \in A\} \subseteq \Gamma^*$ "image of A under h"
- if $B \subseteq \Gamma^*$ then $h^{-1}(B) = \{x \mid h(x) \in B\} \subseteq \Sigma^*$ "preimage of B under h"

Theorem

regular sets are effectively closed under homomorphic image and preimage

Theorem

problems

instance: DFA M and string x	instance: DFA M	instance: DFAs M and N
question: $x \in L(M)$?	question: $L(M) = \varnothing$?	question: $L(M) = L(N)$?

are decidable

Automata

- (deterministic, nondeterministic, alternating) finite automata
- regular expressions
- (alternating) Büchi automata

Logic

- (weak) monadic second–order logic
- Presburger arithmetic
- linear–time temporal logic

Outline

1. Summary of Previous Lecture
2. **Minimization**
3. Intermezzo
4. Weak Monadic Second–Order Logic
5. Further Reading

Example ❶

NFA



$A = \{1\}$ $C = \{1,3\}$ $E = \{1,3,4\}$
$B = \{1,2\}$ $D = \{1,2,4\}$ $F = \{1,4\}$

DFA



not minimal:



Example ❷

DFA



not minimal: states 2 and 3 can be collapsed

Example ❸

DFA



not minimal: states 2 and 3 and states 4 and 5 can be collapsed

Definitions

DFA $M = (Q, \Sigma, \delta, s, F)$

- state p is inaccessible if $\widehat{\delta}(s,x) \neq p$ for all $x \in \Sigma^*$
- states p and q are distinguishable if

$$\left(\widehat{\delta}(p,x) \in F \wedge \widehat{\delta}(q,x) \notin F\right) \vee \left(\widehat{\delta}(p,x) \notin F \wedge \widehat{\delta}(q,x) \in F\right)$$

for some $x \in \Sigma^*$

Minimization Algorithm

DFA $M = (Q, \Sigma, \delta, s, F)$

① remove inaccessible states

② for every two different states determine whether they are distinguishable (marking)

③ collapse indistinguishable states

Marking Algorithm

given DFA $M = (Q, \Sigma, \delta, s, F)$ without inaccessible states

① tabulate all unordered pairs $\{p,q\}$ with $p, q \in Q$, initially unmarked

② mark $\{p,q\}$ if $p \in F$ and $q \notin F$ or $p \notin F$ and $q \in F$

③ repeat until no change:

mark $\{p,q\}$ if $\{\delta(p,a), \delta(q,a)\}$ is marked for some $a \in \Sigma$

Notation

$p \approx q \iff$ states p and q are indistinguishable

Lemma

$p \approx q \iff \{p,q\}$ is unmarked

Example



1					
✓	2				
✓		3			
✓	✓	✓	4		
✓	✓	✓		5	
✓	✓	✓	✓	✓	6

❶ final / nonfinal states are distinguishable

❷ $\{2,6\} \xrightarrow{a} \{4,6\}$ $\{3,6\} \xrightarrow{a} \{5,6\}$

❸ $\{1,4\} \xrightarrow{a} \{2,6\}$ $\{1,5\} \xrightarrow{a} \{2,6\}$

collapse states 2 and 3 and states 4 and 5:



Definition

states p and q of DFA $M = (Q, \Sigma, \delta, s, F)$ are indistinguishable ($p \approx q$) if for all $x \in \Sigma^*$

$$\widehat{\delta}(p,x) \in F \iff \widehat{\delta}(q,x) \in F$$

Lemma

$\approx$ is equivalence relation on Q:

1. $\forall p \in Q \quad p \approx p$ (reflexivity)
2. $\forall p, q \in Q \quad p \approx q \implies q \approx p$ (symmetry)
3. $\forall p, q, r \in Q \quad p \approx q \wedge q \approx r \implies p \approx r$ (transitivity)

Notation

$[p]_\approx = \{q \in Q \mid p \approx q\}$ denotes equivalence class of p

Definition (Collapsing Indistinguishable States)

DFA $M/\approx$ is defined as $(Q', \Sigma, \delta', s', F')$ with

- $Q' = \{[p]_\approx \mid p \in Q\}$
- $\delta'([p]_\approx, a) = [\delta(p,a)]_\approx$ well–defined: $p \approx q \implies \delta(p,a) \approx \delta(q,a)$
- $s' = [s]_\approx$
- $F' = \{[p]_\approx \mid p \in F\}$

Lemma

1. $\widehat{\delta'}([p]_\approx, x) = [\widehat{\delta}(p,x)]_\approx$ for all $x \in \Sigma^*$
2. $p \in F \iff [p]_\approx \in F'$

for all $p \in Q$

Theorem

$L(M/\approx) = L(M)$

Proof

$$x \in L(M/\approx) \iff \widehat{\delta'}([s]_\approx, x) \in F' \iff [\widehat{\delta}(s,x)]_\approx \in F' \iff \widehat{\delta}(s,x) \in F \iff x \in L(M)$$

Question

is $M/\approx$ minimum–state DFA for $L(M)$?

Lemma

$M/\approx$ cannot be collapsed further

Example

DFA for set of strings over $\{a, b\}$ containing at least three occurrences of three consecutive b's, overlapping permitted:



a	b	c	d	e	f	g	h	i	j	k	l
	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓

states d, g and h, k can be merged

Outline

1. Summary of Previous Lecture
2. Minimization
3. **Intermezzo**
4. Weak Monadic Second–Order Logic
5. Further Reading

Particify with session ID **3017 2066**

Question

Which statements about the following DFA A are true ?



- A the DFA is minimal
- ☑ all states can be merged
- C states 2 and 3 are distinguishable
- ☑ states 1 and 2 can be merged

Outline

1. Summary of Previous Lecture
2. Minimization
3. Intermezzo
4. **Weak Monadic Second–Order Logic**
5. Further Reading

Definitions

- first–order variables $V_1 = \{x, y, \dots\}$ ranging over natural numbers
- second–order variables $V_2 = \{X, Y, \dots\}$ ranging over finite sets of natural numbers
- formulas of weak monadic second–order logic

$$\varphi ::= \bot \mid x < y \mid X(x) \mid \neg\varphi \mid \varphi_1 \vee \varphi_2 \mid \exists x.\varphi \mid \exists X.\varphi$$

with $x, y \in V_1$ and $X \in V_2$

Abbreviations

$$\varphi \wedge \psi := \neg(\neg\varphi \vee \neg\psi) \qquad \varphi \to \psi := \neg\varphi \vee \psi$$
$$\forall x.\varphi := \neg\exists x.\neg\varphi \qquad \forall X.\varphi := \neg\exists X.\neg\varphi$$
$$x \leqslant y := \neg(y < x) \qquad x = y := x \leqslant y \wedge y \leqslant x$$
$$\top := \neg\bot \qquad x = 0 := \neg\exists y.\, y < x$$
$$X(0) := \exists x.\ X(x) \wedge x = 0$$

Remarks

- $X(x)$ represents $x \in X$
- MSO is weak MSO without restriction to finite sets

Examples

- $(\forall x.X(x) \to Y(x)) \wedge (\exists y.\neg X(y) \wedge Y(y))$
- $\exists X.(\forall x.x = 0 \to X(x)) \wedge (\forall x.X(x) \to \exists y.x < y \wedge X(y))$
- $\exists X.X(0) \wedge (\forall y.\forall z.z = y+1 \wedge z \leqslant x \to (X(y) \leftrightarrow \neg X(z))) \wedge X(x) \iff x$ is even

Remark

$z = y + 1$ abbreviates $y < z \wedge \neg\exists x.(y < x \wedge x < z)$

Definitions

- assignment α is mapping from variables $x \in V_1$ to $\mathbb{N}$ and $X \in V_2$ to finite subsets of $\mathbb{N}$
- assignment α satisfies formula φ ($\alpha \vDash \varphi$):

$$
\begin{array}{lcll}
\alpha \nvDash \bot & & & \\
\alpha \vDash x < y & \iff & \alpha(x) < \alpha(y) & \\
\alpha \vDash X(x) & \iff & \alpha(x) \in \alpha(X) & \\
\alpha \vDash \neg\varphi & \iff & \alpha \nvDash \varphi & \\
\alpha \vDash \varphi_1 \vee \varphi_2 & \iff & \alpha \vDash \varphi_1 \text{ or } \alpha \vDash \varphi_2 & \\
\alpha \vDash \exists x.\varphi & \iff & \alpha[x \mapsto n] \vDash \varphi & \text{for some } n \in \mathbb{N} \\
\alpha \vDash \exists X.\varphi & \iff & \alpha[X \mapsto N] \vDash \varphi & \text{for some finite subset } N \subset \mathbb{N}
\end{array}
$$

Definitions

- formula φ is satisfiable if $\alpha \vDash \varphi$ for some assignment α
- formula φ is valid if $\alpha \vDash \varphi$ for all assignments α
- model of formula φ is assignment α such that $\alpha \vDash \varphi$
- size of model α is smallest n such that
  1. $\alpha(x) < n$ for $x \in V_1$
  2. $\alpha(X) \subseteq \{0, \ldots, n-1\}$ for $X \in V_2$

Examples

- $(\forall x.X(x) \to Y(x)) \wedge (\exists y.\neg X(y) \wedge Y(y))$ — satisfiable
- $(\forall x.x = 0 \to X(x)) \wedge (\forall x.X(x) \to \exists y.x < y \wedge X(y))$ — unsatisfiable
- $(\exists x.X(x) \wedge \exists y.X(y) \wedge x \neq y) \wedge (\forall x.X(x) \to \exists y.Y(y) \wedge x < y)$ — satisfiable

Definition

given alphabet Σ and string $x = a_0 \cdots a_{n-1} \in \Sigma^*$

- second–order variables $V_2 = \{P_a \mid a \in \Sigma\}$
- $\alpha_x(P_a) = \{i < n \mid a_i = a\}$

Notation

$\underline{x}$ for α_x

Example

$\Sigma = \{a, b\}$

- $\underline{abba}\,(P_a) = \{0, 3\}$
- $\underline{abba}\,(P_b) = \{1, 2\}$

Example

$\Sigma = \{a, b\}$

- $\varphi = \forall x. \neg(P_a(x) \wedge P_b(x))$ — $\underline{x} \vDash \varphi$ for all $x \in \Sigma^*$
- $\psi = \forall x. \forall y. (P_a(x) \wedge P_b(y)) \to x < y$ — $\underline{aabbb} \vDash \psi$ $\underline{aabab} \nvDash \psi$
- $\chi = \forall x. P_b(x) \to \exists y. P_a(y) \wedge y < x$ — $\underline{aaaaa} \vDash \chi$ $\underline{babab} \nvDash \chi$

Definitions

- given alphabet Σ and WMSO formula φ with free variables (exclusively) in $\{P_a \mid a \in \Sigma\}$

$$L(\varphi) = \{x \in \Sigma^* \mid \underline{x} \vDash \varphi\}$$

- set $A \subseteq \Sigma^*$ is WMSO definable if $A = L(\varphi)$ for some WMSO formula φ

Examples

$\Sigma = \{a, b\}$

- regular set $L((a+b)^*ab(a+b)^*)$ is WMSO definable by formula

$$\exists x. \exists y. P_a(x) \wedge P_b(y) \wedge x < y \wedge \neg\exists z. x < z \wedge z < y$$

- WMSO formula

$$\exists x. P_a(x) \wedge \forall y. x < y \to \neg(P_a(y) \vee P_b(y))$$

defines regular set $\{xa \mid x \in \Sigma^*\}$

Theorem

set $A \subseteq \Sigma^*$ is regular if and only if A is WMSO definable

Outline

1. Summary of Previous Lecture
2. Minimization
3. Intermezzo
4. Weak Monadic Second–Order Logic
5. **Further Reading**

Kozen

- Lectures 13 and 14

Important Concepts

- $\alpha \vDash \varphi$
- indistinguishable states
- minimization algorithm
- model
- MSO
- satisfiability
- validity
- weak monadic second–order logic (WMSO)
- WMSO definability

homework for November 13